



Type	4300
	1000 l
	2000 kg
	1000 × 1200 × 1170 mm
	72 kg



For Class I.–IV. Flammables

- ▶ Reinforced steel frame with a rust-resistant finish.
- ▶ Interior container made of physiologically harmless PE-HD enabling easy visibility of the liquid level, scale at 100 l increments.
- ▶ Long life thanks to a new design of the pallet and the steel frame.
- ▶ Simple and safe operation thanks to a drain tap.
- ▶ Compatible with anti-tamper seals, stackable.

Use:

Transport of hazardous substance pursuant to ADR/RID.
Storage of flammable substances with a flash point lower than 55 °C.
Use in facilities with zone 1 and 2 explosion hazard areas.

Accessories

Heating Jackets

- ▶ An ideal solution for quick and efficient heating and draining of liquids and materials.
- ▶ Can come with one, two, or three digital thermostats. A single-zone thermostat can be set within a 0–40 °C range (Type 7538), and a dual- or tri-zone thermostat can be set within a 0–90 °C range.
- ▶ Designed with low weight, long life, and durability in mind.
- ▶ Made of polyester, fitted with adjustable straps for quick fitting and removal. 3 m long power cable (without plug).
- ▶ Silicone insulated coil wound onto a resistive cell.



Type	7538
	4400 × 1000 mm
	230 V
	1300 W



Type	7539
	4400 × 1000 mm
	230 V
	2 × 1000 W



Type	7540
	4400 × 1000 mm
	230 V
	3 × 1000 W

Insulating Lid

- ▶ For faster and more effective heating, it is recommended isolate the IBC tank with a lid (sold separately). The lid is easily mounted to the top of the container.



Type	7541
	1200 × 1000 × 100 mm
	1 kg

Watertight Cover

- ▶ Protects the IBC tank, can be used alongside a heating jacket.



Type	7542
	1000 × 1200 × 1000 mm
	1.5 kg

Insulating Jacket

- ▶ Nylon insulating jacket to better maintain the temperature of the contents of the IBC tank.



Type	7543
	4400 × 1000 mm
	1.5 kg