

For Lubricant

- ▶ The set includes trolley, pneumatic pump, pressure membrane, anti-dust lid, locknut, compressed air filtering unit, 4 m pressure hose, and nozzle with chuck coupling.
- ▶ The set is supplied without a container (can be purchased as an accessory with capacity for 15 to 200 kg of lubricant).
- ▶ Max. pressure 40 MPa.



Type 4973

🗑️ 15 kg
📦 intern. Ø 240–270 mm
⌚ 1500 g/min.

Type 4974

🗑️ 20 kg
📦 intern. Ø 270–310 mm
⌚ 1500 g/min.

Type 6434

🗑️ 50 kg
📦 intern. Ø 335–385 mm
⌚ 1500 g/min.

Type 4975

🗑️ 180–200 kg
📦 intern. Ø 550–600 mm
⌚ 1500 g/min.

Electric

Set for Diesel and Light Fuel Oils

- ▶ Affordable and user-friendly solution.
- ▶ Rotary pump with low consumption.
- ▶ Submersible, self-priming pump for placement in the bottom of a tank.
- ▶ Compact, lightweight design.
- ▶ 4 m dispensing hose with an automatic nozzle.

Type 7388

📦 Ø 56 × 160 mm
⌚ 25 l/min.
⚡ 12 V

Type 7389

📦 Ø 56 × 160 mm
⌚ 25 l/min.
⚡ 12 V / (230 V mains adapter)



Nozzle

Type 8256

⌚ 50 l/min.
⚡ 12 V

Automatic Nozzle

Type 8256-AP

Nozzle

Type 8257 - nozzle

⌚ 50 l/min.
⚡ 24 V

Automatic Nozzle

Type 8257-AP

Nozzle

Type 8258

⌚ 56 l/min.
⚡ 230 V

Automatic Nozzle

Type 8258-AP



- ▶ Can be fitted with a flow meter (Type 8299).