


# Pumps


## Sets for Diesel and Light Fuel Oils

- ▶ 1600 mm suction hose.
- ▶ 5–20 mPas viscosity range.
- ▶ 160 cm suction hose with a filter and 4 m dispensing hose, nozzle and 2" thread for mounting onto a drum.
- ▶ Integrid manual pump.



### Type 6681

 2" connection

 36 l/min.


 230 V

### Digital Flow Meter

#### Type 6682

- Two-line display.
- Indicator of current and overall offtake, with memory.
- Designed for in-house dispensing.
- Guaranteed deviation of  $\pm 1-2\%$  at offtake of 5–90 l/min.

### Type 6683

 2" connection

 55 l/min.

 230 V


### Digital Flow Meter


#### Type 6684

- Two-line display.
- Indicator of current and overall offtake, with memory.
- Designed for in-house dispensing.
- Guaranteed deviation of  $\pm 1-2\%$  at offtake of 5–90 l/min.



### Type 6685

 2" connection

 80 l/min.

 230 V

### Digital Flow Meter


#### Type 6686


- Two-line display.
- Indicator of current and overall offtake, with memory.
- Designed for in-house dispensing.
- Guaranteed deviation of  $\pm 1\%$  at offtake of 5–90 l/min.

- ▶ For pumping oils up to a viscosity of 200–2000 mPas.
- ▶ 840 mm suction tube, 4 m dispensing hose and nozzle.



### Type 6687

 2" connection

 25 l/min.

 230 V

### Digital Flow Meter

#### Type 6688

- Two-line display.
- Indicator of current and overall offtake, with memory.
- Designed for in-house dispensing.
- Guaranteed deviation of  $\pm 1\%$  at offtake of 5–25 l/min.