

Fuel Stations

large-capacity

Universal, for Diesel and Fuel Oil

- ▶ Polyethylene container – fitted with a galvanised housing which serves as a spill tray.
- ▶ Can be handled using a pallet truck or forklift.
- ▶ Certified for placement in enclosed spaces.
- ▶ Automatic nozzle, 6 m hose (4.5 m dispensing hose, 1.5 m suction hose), level gauge, and integridd handles.
- ▶ Can be fitted with a flow meter (Type 4276).

Type 4275-AP

1000 l

770 × 1280 × 1420 mm

92 kg

30 l/min.

230 V



Universal Assemblies for Diesel and Fuel Oil

- ▶ Assembles delivered along with a connecting kit.
- ▶ Containers made of polyethylene – fitted with a galvanised housing which serves as a spill tray.
- ▶ Certified for use in enclosed spaces.
- ▶ 4 m dispensing hose, automatic nozzle, holder, digital flow meter, and opening for refilling from a storage tank.

Type 7295

1500 l

2010 × 770 × 2020 mm

176 kg

50 l/min.

230 V

Type 7296

3000 l

2010 × 1570 × 2020 mm

330 kg

50 l/min.

230 V

Type 7297

4500 l

2010 × 2370 × 2020 mm

480 kg

50 l/min.

230 V



Mobile

- ▶ Mobile, double-walled, hot-dip galvanised fuel station made of 3 mm thick sheet metal.
- ▶ Certified for use in buildings and in open spaces without the need for a spill tray. Strong enough to withstand an explosion.
- ▶ Container certified in line with ADR for transporting hazardous liquids.
- ▶ Electric pump with EX rating – explosion-proof design; flow rate meter, automatic nozzle, 3.4 m dispensing hose, lockable pump housing, forklift pockets, level gauge.

Type 4282

980 l

1200 × 1200 × 1770 mm

310 kg

50 l/min.

230 V

