

Fuel Stations

large-capacity

Double-Walled

- ▶ Special double-walled design also functions as a spill tray.
- ▶ Peripheral metal reinforcement ensures mechanical resistance.
- ▶ Pockets for ease-of-handling by forklift.
- ▶ Optical indication of damage to interior container, filling opening with TW coupling and limit switch, bleed valve, level gauge, automatic nozzle with holder, 4 m dispensing hose (Type 7216 with 8 m hose).



Lidless – Indoor

Type 7214

| |
|-----------------------|
| 2500 l |
| 1200 × 1800 × 1740 mm |
| 220 kg |
| 230 V |
| 72 l/min. |

With Lid – Outdoor

Type 7215

| |
|-----------------------|
| 2500 l |
| 1200 × 1800 × 1800 mm |
| 235 kg |
| 230 V |
| 72 l/min. |

With Lid and Flow Meter

Type 7216

| |
|-----------------------|
| 2500 l |
| 1200 × 1800 × 1800 mm |
| 255 kg |
| 230 V |
| 72 l/min. |



Outdoor

- ▶ With double-walled structure.
- ▶ With lid for outdoor use.
- ▶ Can be extended with a supplementary unit to increase capacity.

Type 8152

| |
|-----------------------|
| 5000 l |
| 2400 × 2300 × 1850 mm |
| 205 kg |
| 230 V |
| 72 l/min. |

- With lid and 4 m hose.

Type 8153

| |
|-----------------------|
| 5000 l |
| 2400 × 2300 × 1850 mm |
| 230 kg |
| 230 V |
| 72 l/min. |

- With lid, K33 flow meter, filter with water separator, and 8 m hose with reel.

Type 8154 (supplementary unit)

| |
|-----------------------|
| 5000 l |
| 2400 × 2300 × 1850 mm |
| 201 kg |
| 230 V |
| 72 l/min. |

- With visual indicator, filling connector for storage tanks, indicator to prevent overfilling, bleed valve, level gauge, suction hose with kit for connecting to the base tank.

