

Fuel Stations large-capacity

For Diesel

Internal

- ▶ Aboveground station for dispensing diesel fuel.
- ▶ Double-layered structure made of high-quality polyethylene (resistant to UV radiation), performs the function of a spill tray.
- ▶ Simple to install in an open space.
- ▶ K600 B/3 digital flow meter.
- ▶ 6 m dispensing hose, automatic nozzle, glass filter with water separator.
- ▶ 2" filling piping located inside the casing.
- ▶ Mechanical safety against overfilling (Spill-Stop).
- ▶ UNIRx level sensor (measures in litres), sensor for detecting leakage into the interlayer, GOK maximum level sensor.
- ▶ LED lighting with a motion sensor.

Optional accessories:

- ▶ Flow meter with option to record up to 1500 users.
- ▶ Computer software capable of creating detailed reports on fuel consumption.
- ▶ Pump with output of up to 100 l/min.
- ▶ 12 m dispensing hose.
- ▶ Protective steel frame, and more...



Type 3556

2500 l
2460 × 1460 × 1850 mm
250 kg
79 l/min.
230 V

Type 3557

5000 l
2850 × 2230 × 2340 mm
320 kg
79 l/min.
230 V

Type 3558

9000 l
3250 × 2450 × 2950 mm
490 kg
79 l/min.
230 V

