

Fuel Stations mobile

For Diesel

- ▶ Approved for transport and immediate use in line with ADR.
- ▶ Polyethylene container with integridd handle and holders.
- ▶ Fitted with tubed wheels with a diameter of 300 mm, filling neck with integridd bleed, breakwater, nozzle holder, and mouldings for fastening straps for transport.
- ▶ Self-priming electric pump with automatic nozzle and a 3 m dispensing hose; type 7212 also comes with 4 m power cable.

Type 7212

100 l
1000 × 590 × 430 mm
20 kg
30 l/min.
12 V

Version with Manual Pump

Type 7213
100 l
1000 × 590 × 430 mm
20 kg
25 l/min.



- ▶ Approved for transport and immediate use in line with ADR.
- ▶ Single-walled polyethylene containers.
- ▶ Fitted with a nozzle holder, filling opening and ventilation.
- ▶ Includes a self-priming electric pump (12 or 24 V with output of 25 or 40 l/min. a 4 m dispensing hose and 4 m electric cable).
- ▶ Integridd forklift pockets.
- ▶ Can be stacked without the need to remove the pump or accessories.
- ▶ Improved safety during transport thanks to a valve that enables completely closing off the tank.



Type 3982

125 l
800 × 600 × 450 mm
24 kg
Rec. flow meter A
12 V
25 l/min.

Type 8051

210 l
785 × 595 × 685 mm
22 kg
Rec. flow meter A
12 V
40 l/min.

Type 8053

440 l
1180 × 800 × 710 mm
35 kg
Rec. flow meter A
12 V
40 l/min.

Type 3985

600 l
1160 × 800 × 1020 mm
53 kg
Rec. flow meter B
12 V
40 l/min.

Type 3986

600 l
1160 × 800 × 1020 mm
53 kg
Rec. flow meter B
24 V
40 l/min.

Station Lids

Type 3987

Type 8052

Type 8054

Type 3988

