

- ▶ Can be placed on the body of lorry or van,
- ▶ Safe and legal transport of fuel in line with ADR regulations for international transport of dangerous goods.
- ▶ Made of UV-stable medium-density polyethylene; stable colour, does not crack.

- ▶ 4 m hose, nozzle with a shut-off valve, suction hose with filter, 2" filling neck with external thread.
- ▶ Digital flow meter (permissible deviation of measurement: $\pm 0.5\%$).
- ▶ Float fuel level gauge.
- ▶ Ventilation secured against spillage during transport.
- ▶ Lockable cover against weather and unauthorised access.



| |
|---------------------|
| Type 3344 |
| 430 l |
| 1180 × 860 × 910 mm |
| 55 kg |
| 35 l/min. |
| 12 V |

| |
|---------------------|
| Type 3345 |
| 430 l |
| 1180 × 860 × 910 mm |
| 55 kg |
| 35 l/min. |
| 24 V |

| |
|---------------------|
| Type 3346 |
| 430 l |
| 1180 × 860 × 910 mm |
| 55 kg |
| 56 l/min. |
| 230 V |

| |
|-----------------------|
| Type 3347 |
| 900 l |
| 1410 × 1050 × 1210 mm |
| 98 kg |
| 35 l/min. |
| 12 V |

| |
|-----------------------|
| Type 3348 |
| 900 l |
| 1410 × 1050 × 1210 mm |
| 98 kg |
| 35 l/min. |
| 24 V |

| |
|-----------------------|
| Type 3349 |
| 900 l |
| 1410 × 1050 × 1210 mm |
| 98 kg |
| 56 l/min. |
| 230 V |

