

# Containers

## storage containers

### With Spill Tray



- ▶ The floor consists of a hot-dip galvanised tray made of 3 mm thick sheet metal, and a hot-dip galvanised grid.
- ▶ The container can be used to store flammables with a flash point above 100 °C.
- ▶ Maximum capacity for petroleum products and flammables: 2000 l.
- ▶ The container is fitted with double-wing doors with a handle and lock on the front.
- ▶ 1930 × 1930 mm doorway when the doors are fully open.

Type	<b>4347</b>
	275 l (spill tray)
	3000 × 2200 × 2200 mm
	605 kg

### Shelters

- ▶ The construction of the shelters and garages consists of load-bearing profiles made of 2 mm galvanised sheets. The walls are made of trapezoidal sheets with thickness of 0.75 mm. Assembled containers can be transported by crane or forklift.
- ▶ For suspending by crane, each corner is fitted with crane lugs. The floor of the shelter is made up of 35 mm thick wooden planks with tongue and groove joints.
- ▶ Floor load capacity 500 kg/m<sup>2</sup>. Universal shelters and mobile garages are supplied disassembled.

#### Universal

- ▶ Suitable as a shed for the garden, workshop, or as a shelter for waste containers.

#### Mobile Garage

- ▶ Fitted with double-wing doors on the short side for driving into the garage and double-wing doors on the long side to exit the vehicle.
- ▶ The doors are fitted with a cylindrical lock and handle.



Type	<b>4878</b>
	2250 × 2200 × 2200 mm
	395 kg

Type	<b>4879</b>
	4000 × 2200 × 2200 mm
	560 kg

Type	<b>4880</b>
	6000 × 2200 × 2200 mm
	780 kg

Type	<b>4881</b>
	5000 × 2200 × 2200 mm
	720 kg