- ► For bulk material.
- ► Handle by forklift, or manually.
- ► The body is secured against spontaneous tipping.
- Thickened edge improves the rigidity of the container.
- Fitted with 3 castors with a diameter of 200 mm (2× fixed, 1× swivel castor with brake).

- Suitable for collecting and handling metal shavings from machine tools.
- Consists of an undercarriage and a body.
- The body is secured against spontaneous tipping by a safety.
- The bottom of the container features a drain tap with a sieve.
- The undercarriage is fitted with polyamide castors – the front castors are fixed, the back castors swivel and include a brake and directional lock.
- For shavings generated during the machining of metals with oily waste.
- Tipping by pedal, and held in the closed position.
- Coarse dirt is filtered from oil through a sieve located in the bottom of the container.
 Oil is then drained using a valve
- in the bottom section of the container.Easy to handle thanks to 4 castors
- with a diameter of 100 mm (2 fixed and 2 swivel).



Type 7364		
$\bigcirc \downarrow$	1050 × 580 × 980 mm	
2	75 kg	
Ş	600 kg	
0	2501	



Type 7348		
$\bigcirc \downarrow$	873×624×889 mm	
2	40 kg	
<u>Ş</u>	500 kg	
0	1301	



Туре 7294		
\bigcirc	970×660×895 mm	
2	32.7 kg	
Ş	300 kg	
0	801	



Available in other colours on request.