- ► Fitted with a central interlock mechanism to prevent multiple drawers opening.
- ► Top fitted with a rubber pad.
- ► Perforated sections of the trolley enable tool holders to be fitted from the inside or the outside.
- Equipment: 2 × swivel castors with brake, 2 × fixed castors.
- ▶ Powder coated (RAL 7035 grey, RAL 5012 blue).







Туре 3422		
$\bigotimes_{i \neq i}$	750×500×940 mm	
$\Box$	44 kg	
ç	150 kg / 30 kg (per shelf)	

Туре 3423				
$\bigcirc$	750 × 500 × 940 mm			
$\Box$	49.6 kg			
ç	150 kg / 30 kg (per shelf)			



Type <b>3424</b>		
$\bigcirc$	750×500×940 mm	
6	59.4 kg	
Ç	150 kg / 30 kg (per shelf)	



7		U

Type <b>3425</b>		
$\bigcirc$	750 × 500 × 920 mm	
$\Box$	80.3 kg	
Ç	300 kg / 80 kg (per drawer)	



- Type 3426
- 곱 86 kg
- Ω 300 kg / 80 kg (per drawer)

## Drawer Dividers (for Type 3425 and 3426 trolleys)

► For 60–120 mm tall drawers





Type 3485

Type 3484

▶ For 150–240 mm tall drawers.





Type **3486** 

Type **3487**