

# Emergency Showers and eyewash stations

- ▶ Ensure effective first aid in case of burns, acid burns, or scalding. Suitable for places where workers come into contact with hazardous substances (laboratories, workshops, hospitals, swimming pools with chlorination, universities, schools, etc).
- ▶ Made of steel with galvanised pipes, with a green epoxy coat for long life even in highly aggressive environments.
- ▶ Controlled via a mechanism with a chrome-nickel valve, connectors made of brass.
- ▶ Recommended water temperature: 15–35 °C.

## Wall-Mounted Eyewash Stations



Type **3948**

📏 320 × 75 × 410 mm

📦 1.5 kg



Type **7589**

📏 260 × 260 × 284 mm

📦 10 kg



Type **7590**

📏 260 × 260 × 284 mm

📦 10 kg

## Wall-Mounted Showers



Type **7592**

📏 590 × 2350 mm

📦 11 kg

- ▶ Includes two saline bottles with 500 ml capacity (approx. 4 min. of rinsing) and a mirror.

- ▶ Basin material: polypropylene / stainless steel.
- ▶ Recommended water temperature: 15–35 °C.

## Free-Standing Eyewash Stations and Combined Showers



Type **7591**

📏 260 × 260 × 1020 mm

📦 11 kg



Type **7593**

📏 2150 mm (height)

📦 15 kg

EN  
15154-1

EN  
15154-2



**Saline Solution 500 ml**

Type **3948-A**



- ▶ Eyewash station controlled by hand or foot pedal; mounted on the floor.
- ▶ Basin material: polypropylene.

- ▶ The combined shower mounts on the floor.
- ▶ Basin and shower head made of polypropylene.

- ▶ Refill (for Type 3948).