## **Speed Bumps** and cable ramps



- ► For reducing vehicle speed.
- ► The bumps are made up of continuous and edge segments made of recyclate.
- ► All segments are fitted with reflective elements to improve visibility.
- ► Mounted to the road using rawlplugs.
- ► Comes with galvanised screws, rawlplugs and brace rods.





Continuous Piece (Yellow)			
Type <b>4355</b>			
Continuous Piece (Black)			
Type <b>4356</b>			
$\overline{\Diamond}$	500 × 430 × 30 mm		
2	6.2 kg		
	Recom. speed 30 km/h		

Endpiece (Yellow) Type 4357 Endpiece (Black)						
					Туре	4358
					$\overline{\mathbb{G}}$	215 × 430 × 30 mm
<u> </u>	1.9 kg					
	Recom. speed 30 km/h					

Continuous Piece (Yellow)				
Type <b>4359</b>				
Con	tinuous Piece (Black)			
Туре	4360			
$\Diamond$	500 × 430 × 50 mm			
3	10.2 kg			
	Recom. speed 20 km/h			

Endpiece (Yellow)				
Type <b>4361</b>				
End	piece (Black)			
Туре	4362			
$\bigcirc$	215 × 430 × 50 mm			
5	2.8 kg			
	Recom. speed 20 km/h			

Continuous Piece (Yellow)		Endpiece (Y	
Type 4363 Continuous Piece (Black)		Type <b>4365</b>	
		Endpiece (E	
Туре	4364	Тур	4366
$\overline{\Diamond}$	500 × 430 × 60 mm	$\bigcirc$	215×4
	13 kg	<u> </u>	3.7 kg
	Recom. speed 10 km/h		Recom

N)	Endpiece (Yellow)			
	Type <b>4365</b>			
:)	Endpiece (Black)			
	Type <b>4366</b>			
	215×430×60 mm			
	子 3.7 kg			
/h	Recom. speed 10 km/l	า		
		_		



- ► Used to protect cables or hoses laid across a road.
- Made up of a main arched piece and an insert. Laid freely across the road without the need for further mounting.

## Arched Piece

Type **4367** 

\$\operatorname{\text{\operatorname}} 800 × 600 × 80 mm

24.6 kg

## Incort

800×170×50 mm

4.8 kg



**332** en.mevatec.cz