

Trucks

pallet trucks

Manual


- ▶ Designed for handling pallets sized 1200 × 800 mm, or 800 × 600 mm, with a pick-up clearance of 100 mm.
- ▶ Sturdy frame carried by a rotary chassis on one end and small wheels on the other.
- ▶ Moving the tow bar up and down activates the hydraulics, the control valve has three positions: 1 lifting, 2 neutral, 3 lowering.




With Polyurethane Wheels

- ▶ Ø 200 mm control wheels with cast iron wheels and polyurethane tyres.
- ▶ For temperatures from -20 °C to +75 °C.
- ▶ Paired Ø 80 mm wheels on the fork for flawless operation on uneven surfaces.

Type **5253-P**

 1150 × 540 mm (fork)

 2500 kg


 67 kg




With Rubber Wheels

- ▶ Ø 200 mm control wheels with cast iron wheels and rubber tyres.
- ▶ For temperatures from -10 °C to +60 °C.
- ▶ Paired Ø 80 mm wheels on the fork for flawless operation on uneven surfaces.

Type **5253-G**

 1150 × 540 mm (fork)

 2500 kg


 67 kg




Low-Profile

- ▶ Designed primarily for handling pallets with low ground clearance.
- ▶ Minimum fork height of 51 mm, maximum height of 161 mm.
- ▶ Comes with polyurethane wheels by default.

Type **4672**

 1150 × 540 mm (fork)

 1500 kg

 92 kg
