

## With Plastic Wheel

- ▶ Fixed castors, swivel castors and swivel castors with brake.
- ▶ Plastic wheel and rubber tyre.
- ▶ Reinforced steel fork with galvanised finish.
- ▶ Wide range of uses on a variety of handling equipment.



	Type							
<b>Fixed</b>	<b>6340</b>	80 mm	35 mm	70 kg	108 mm	103 × 85 mm	80/77 × 60 mm	9 mm
	<b>6341</b>	100 mm	35 mm	75 kg	128 mm	103 × 85 mm	80/77 × 60 mm	9 mm
	<b>6342</b>	125 mm	37 mm	100 kg	155 mm	103 × 85 mm	80/77 × 60 mm	9 mm
	<b>6343</b>	160 mm	40 mm	135 kg	200 mm	137 × 115 mm	105 × 80/75 mm	11 mm
	<b>6344</b>	200 mm	50 mm	205 kg	240 mm	137 × 115 mm	105 × 80/75 mm	11 mm
<b>Swivel</b>	<b>6345</b>	80 mm	35 mm	70 kg	108 mm	105 × 85 mm	80/77 × 60 mm	9 mm
	<b>6346</b>	100 mm	35 mm	75 kg	128 mm	105 × 85 mm	80/77 × 60 mm	9 mm
	<b>6347</b>	125 mm	37 mm	100 kg	155 mm	105 × 85 mm	80/77 × 60 mm	9 mm
	<b>6348</b>	160 mm	40 mm	135 kg	200 mm	137 × 105 mm	105 × 80/75 mm	11 mm
	<b>6349</b>	200 mm	50 mm	205 kg	240 mm	137 × 105 mm	105 × 80/75 mm	11 mm
<b>Swivel with brake</b>	<b>6350</b>	80 mm	35 mm	70 kg	108 mm	105 × 85 mm	80/77 × 60 mm	9 mm
	<b>6351</b>	100 mm	35 mm	75 kg	128 mm	105 × 85 mm	80/77 × 60 mm	9 mm
	<b>6352</b>	125 mm	37 mm	100 kg	155 mm	105 × 85 mm	80/77 × 60 mm	9 mm
	<b>6353</b>	160 mm	40 mm	135 kg	200 mm	137 × 105 mm	105 × 80/75 mm	11 mm
	<b>6354</b>	200 mm	50 mm	205 kg	240 mm	137 × 105 mm	105 × 80/75 mm	11 mm

## Polyamide

- ▶ Fixed castors, swivel castors and swivel castors with brake.
- ▶ Polyamide wheel and galvanised steel fork.
- ▶ Suitable for handling on a smooth surface.



	Type							
<b>Fixed</b>	<b>6355</b>	80 mm	34 mm	200 kg	108 mm	103 × 85 mm	80/77 × 60 mm	9 mm
	<b>6356</b>	100 mm	36 mm	200 kg	128 mm	103 × 85 mm	80/77 × 60 mm	9 mm
	<b>6357</b>	125 mm	40 mm	275 kg	155 mm	103 × 85 mm	80/77 × 60 mm	9 mm
	<b>6358</b>	160 mm	40 mm	350 kg	200 mm	137 × 115 mm	105 × 80/75 mm	11 mm
	<b>6359</b>	200 mm	46 mm	350 kg	240 mm	137 × 115 mm	105 × 80/75 mm	11 mm
<b>Swivel</b>	<b>6360</b>	80 mm	34 mm	200 kg	108 mm	105 × 85 mm	80/77 × 60 mm	9 mm
	<b>6361</b>	100 mm	36 mm	200 kg	128 mm	105 × 85 mm	80/77 × 60 mm	9 mm
	<b>6362</b>	125 mm	40 mm	275 kg	155 mm	105 × 85 mm	80/77 × 60 mm	9 mm
	<b>6363</b>	160 mm	40 mm	350 kg	200 mm	137 × 105 mm	105 × 80/75 mm	11 mm
	<b>6364</b>	200 mm	46 mm	350 kg	240 mm	137 × 105 mm	105 × 80/75 mm	11 mm
<b>Swivel with brake</b>	<b>6365</b>	80 mm	34 mm	200 kg	108 mm	105 × 85 mm	80/77 × 60 mm	9 mm
	<b>6366</b>	100 mm	36 mm	200 kg	128 mm	105 × 85 mm	80/77 × 60 mm	9 mm
	<b>6367</b>	125 mm	40 mm	275 kg	155 mm	105 × 85 mm	80/77 × 60 mm	9 mm
	<b>6368</b>	160 mm	40 mm	350 kg	200 mm	137 × 105 mm	105 × 80/75 mm	11 mm
	<b>6369</b>	200 mm	46 mm	350 kg	240 mm	137 × 105 mm	105 × 80/75 mm	11 mm