

# Transport and Machine Wheels

## With Metal Wheel

### With Rubber Tyre

- ▶ Aluminium wheel, rubber tyre, ball bearing.
- ▶ Suitable for uneven surfaces.

Load capacity up to 500 kg



	Type							
Fixed	<b>6580</b>	160 mm	50 mm	350 kg	200 mm	137 × 115 mm	105 × 80 mm	11 mm
	<b>6581</b>	200 mm	50 mm	450 kg	240 mm	137 × 115 mm	105 × 80 mm	11 mm
	<b>6582</b>	250 mm	50 mm	500 kg	290 mm	137 × 115 mm	105 × 80 mm	11 mm
Swivel	<b>6583</b>	160 mm	50 mm	350 kg	200 mm	137 × 105 mm	105 × 80 mm	11 mm
	<b>6584</b>	200 mm	50 mm	450 kg	240 mm	137 × 105 mm	105 × 80 mm	11 mm
	<b>6585</b>	250 mm	50 mm	500 kg	290 mm	137 × 105 mm	105 × 80 mm	11 mm
Swivel with brake	<b>6586</b>	160 mm	50 mm	350 kg	200 mm	137 × 105 mm	105 × 80 mm	11 mm
	<b>6587</b>	200 mm	50 mm	450 kg	240 mm	137 × 105 mm	105 × 80 mm	11 mm
	<b>6588</b>	250 mm	50 mm	500 kg	290 mm	137 × 105 mm	105 × 80 mm	11 mm

## With Polyurethane Tyre

- ▶ Aluminium wheel, polyurethane tyre, ball bearing.
- ▶ Advantage of high load capacity.
- ▶ Unsuitable for uneven surfaces.

Load capacity 800 kg



	Type							
Fixed	<b>6589</b>	160 mm	50 mm	800 kg	200 mm	137 × 115 mm	105 × 80 mm	11 mm
	<b>6590</b>	200 mm	50 mm	800 kg	240 mm	137 × 115 mm	105 × 80 mm	11 mm
	<b>6591</b>	250 mm	55 mm	800 kg	290 mm	137 × 115 mm	105 × 80 mm	11 mm
Swivel	<b>6592</b>	160 mm	50 mm	800 kg	200 mm	137 × 105 mm	105 × 80 mm	11 mm
	<b>6593</b>	200 mm	50 mm	800 kg	240 mm	137 × 105 mm	105 × 80 mm	11 mm
	<b>6594</b>	250 mm	55 mm	800 kg	290 mm	137 × 105 mm	105 × 80 mm	11 mm
Swivel with brake	<b>6595</b>	160 mm	50 mm	800 kg	200 mm	137 × 105 mm	105 × 80 mm	11 mm
	<b>6596</b>	200 mm	50 mm	800 kg	240 mm	137 × 105 mm	105 × 80 mm	11 mm
	<b>6597</b>	250 mm	55 mm	800 kg	290 mm	137 × 105 mm	105 × 80 mm	11 mm

## With Polyurethane Tyre

- ▶ Cast iron wheel, polyurethane tyre, ball bearing.
- ▶ Extreme load capacity.

Load capacity 1,200 kg



	Type							
<b>F</b>	<b>6601</b>	200 mm	50 mm	1200 kg	245 mm	135 × 110 mm	105 × 80/75 mm	11 mm
<b>S</b>	<b>6602</b>	200 mm	50 mm	1200 kg	245 mm	135 × 110 mm	105 × 80/75 mm	11 mm
<b>SB</b>	<b>6603</b>	200 mm	50 mm	1200 kg	245 mm	135 × 110 mm	105 × 80/75 mm	11 mm